

# **XLON**<sup>®</sup> PC XSL









## Description

The **XLON**<sup>®</sup> PC XSL is a versatile usable touchpanel computer offering an extravagant design with its satined glass frame. The frame also can be left for mounting the touchpanel computer behind a cabinet door.



The **XLON**<sup>®</sup> PC XSL is designed for highest availability and reliability, which is most important in automation systems. Therefore only high quality parts are selected for the **XLON**<sup>®</sup> PC XSL. Moreover, fanless systems with ultra-low power CPU and FlashDisk eliminate the need of mechanical rotating parts like fan and harddisk.

## Features and Benefits

-  Low-cost touchpanel computer optimised for Building Automation
-  7" color TFT touchpanel with excellent viewing angle
-  High availability due to FlashDisk and fanless operation
-  LonTalk<sup>®</sup> adapter with TP/FT transceiver as option
-  Microsoft Windows CE .net platform
-  Microsoft Internet Explorer 6 for web-based applications
-  Rapid application programming on .net framework
-  Rapid LON interface programming with **XLON**<sup>®</sup> HAPI library

The **XLON**<sup>®</sup> PC XSL supports all common PC interfaces like USB host, Ethernet and COM. In addition to it supports a USB slave and an optional LonTalk port with TP/FT transceiver.

The **XLON**<sup>®</sup> PC XSL runs on Microsoft Windows CE operating system supporting .net compact framework and Internet Explorer 6. This offers the user a wide range of powerful applications using Internet or .net technology. The system can even act as embedded web server for smaller systems.

## Specifications

Processor	Intel® XScale® PXA270 processor @ 312MHz (520MHz as option)
RAM	64 MB SDRAM (up to 128 MB available)
Memory	32 MB FlashDisk (up to 64 MB available)
Memory Card	SD/MMC expansion slot available as option
Ethernet	10/100 BaseT RJ45
USB	USB Host port / USB Slave port
Serial	RS232 Port as option
LonTalk® Interface	TP/FT10 as option, with Service LED and button
Display	7.0" WVGA color TFT display, 800 x 480 pixels, LED backlight, brightness 330cd/m <sup>2</sup>
Touch	4-wire resistive touch incl. controller
Mechanics	Top quality housing Satined Glass frame Fanless design
Power Supply	24VDC +/-25% @ 7W typ.
General	Operating temperature 0°C ... 50°C CE mark
Operating System	Windows CE 5.0
Software	User application preinstalled (optional) Internet explorer in kiosk mode preconfigured (optional) <b>XLON<sup>®</sup> HAPI</b> preinstalled (optional)

## Ordering Information

XLON® PC XSL	Article Number XSL-312-64-32-7.0-CE5.0
--------------	---